



Product features

- Industrial grade design, equipped with 4G modules;
- 4G to wired to WIFI signal conversion, meeting various application scenarios;
- With a large number of devices, it is easy to connect to various wireless

HUASIFEI Industrial grade intelligent 4G router WS300A

terminal devices;

- No wiring, bid farewell to wired broadband, flexible installation;
- Free card replacement, plug and play, with network access for card insertion;
- Two 2.4G and two 4G high gain omnidirectional antennas are installed externally, with strong penetration and stable signal.

Product specifications

product name	Industrial grade intelligent 4G router			
product model	WS300A			
Hardware specifications				
hardware system	master control	MT7620A		
	FLASH	16MB		
	DDR	128MB		
	4G module	EC200A/EC20/EC25/EP06		
Wireless parameters	Protocol standards	IEEE 802.11 b/ g/ n		
	Working frequency	2.4GHz: 2412MHz~2472MHz		
	band			
	Wireless rate	300Mbps Max		
	4G rate	LTE-FDD: B1/B3/B5/B7/B8/B20/B28		
		LTE-TDD: B38/B40/B41		
		WCDMA: B1/B5/B8		
		GSM: B3/B8		
	Transmission power	18dBm Max		
physical interface	network interface	1 10/100 Mbps RJ45 Ethernet WAN port		

HUASIFEI Industrial grade intelligent 4G router WS300A

		4 10/100 Mbps RJ45 Ethernet LAN ports
	Power supply	1 DC power port, supporting 12V DC power supply
	interface	The power port, supporting 12 vibe power suppry
	SIM card interface	1 standard pop-up Mini SIM card slot
	Key switch	1 RESET reset button
	- Ney officers	2 standard SMA interfaces for 4G antennas (external
	Antenna interface	interface, interchangeable with different antennas)
		2 WIFI antenna standard SMA interfaces (external interface,
		can replace different antennas)
pilot lamp	LED indicator light	Respectively POWER, 4G, WIFI, WAN, LAN1, LAN2, LAN3,
poc idilip	LED marcator ngm	LAN4
	Power supply	DC 12V~1A power supply
Power supply/power	method	55 - 2. Троиз. зарр.,
consumption	Whole machine	< 6W
	power	
	main engine	Industrial grade intelligent 4G router host * 1
	DC adapter	DC 12V/1A
product accessories	antenna	Two 5dBi high gain omnidirectional WIFI antennas
product decessories		Two 5dBi high gain omnidirectional 4G antennas
		User manual * 1, warranty card * 1, certificate of conformity
	other	* 1
		External dimensions (length * width * height): 110mm *
	Product size	90mm * 30mm (excluding antenna)
		Antenna height: 190mm
Appearance/Packaging	Appearance	Iron shell, frosted surface
	material	inon shelly mosted surface
	Appearance color	Black (customizable appearance color)
	weight	< 1.5kg
	Protection level	IP31, 2KV lightning protection
	Installation method	Desktop and wall mounted
	mistanation method	Working temperature: -10 °C~55 °C
other	Usage environment	Storage temperature: -40 °C~70 °C
		Working humidity: 10%~90% RH non condensing
		Storage humidity: 5%~95% RH non condensing
Software specifications		
network	WAN access	wired 4G
	WAN access method	wired、4G
	External address	support
	detection	συμμοτί
	External network	support
		συμμοτί
	status display	support
	LAN settings	support
	DHCP server	support

HUASIFEI Industrial grade intelligent 4G router WS300A

	Display of	support
	uplink/downlink	
	speed	
4G dialing	4G dialing method	Auto/Manual
	MAC Address Clone	support
	4G signal strength	support
	display	
	4G module IMEI	support
	recognition	
	SIM card number	support
	display	
	Wireless switch	support
	SSID settings	support
	SSID hidden	support
	User isolation	support
Wireless settings	Wireless channel	support
	settings	
	Transmission power	support
	setting	
	Encryption method	WPAPSK, WPA2PSK, WPAPSKWPA2PSK
	Encryption type	TKIP, AES, TKIPAES
	Visitor control	support
	QoS settings	support
advanced setting	Static routing	support
		Support DMZ settings, port mapping, terminal
	firewall	management, MAC filtering, etc
	system	Supports firmware upgrades, scheduled restarts, firmware
	management	file import and export, etc
	System Tools	PING detection, routing tracking, DHCP detection